

MODEL	DIGI-35A	DIGI-185	DIGI-360	4025	3002A	303D	3670	3012A	6020	2555A	3002D	303DM
Output Voltage	0-30V	0-18V	0-30V	0-20V	0-30V	0-30V x 2	0-18V/0-36V	0-30V	0-60V	0-25V x 2 & 5V Fixed	0-30V	0-30V x 2
Output Current	0-3A	0-5A	0-6A	0-25A	0-2A	0-3A x 2	0-7A/0-3.5A	0-12A	0-2A	0-500mA x 2 & 3A	0-2A	0-3A x 2
Voltage Regulation												
Load	0.05% from zero to full load										0.1% from zero to full load	0.05% from 0 to full load
Line	0.02% from 105 to 125 VAC										0.035% from 105 to 125 VAC	0.02% from 105 to 125 VAC
Current Regulation												
Load	0.25% from zero to rated V									NA	2.5% from short circuit to 30V	0.25% from short circuit to 30V
Line	0.1% from 105 to 125VAC									NA	0.3% from 105 to 125 VAC	0.1% from 105 to 125 VAC
Ripple & Noise	<1mV RMS										2.5mV RMS	<2mV RMS
Metering (V & A)	3 Digit 0.5" LED					Analog					Digital LCD	Digital LCD x 2
Accuracy	+/- 0.5% of rdg +/- 2 dgt					2% FS					<+/-2% FS	<+/-2% FS
Temperature Operating/Storage	0 to 40 degrees C, <75% R.H.										0 to 40° C/-20° to +75°C	0 to 40° C/-20° to +75°C
Power Requirements	115/230 +/- 10/20 VAC, 50/60 Hz (fuse in-line)										115/230 ± 10/20 VAC, 50/60 Hz, 170VA	115/230 +/- 10/20 VAC, 50/60 Hz
Power Consumption	180W	190W	350W	1065W	125W	315W	335W	670W	240W	115W	125W	315W
Size	5.5 x 6.5 x 10.4 in.	5.5 x 6.5 x 10.4 in.	5.5 x 12.1 x 10.5 in	5.75 x 19 x 12.75 in.	4.3 x 8 x 8.3 in.	5.5 x 12.1 x 10.5 in.	5.5 x 12.1 x 10.5 in.	5.75 x 19 x 13.5 in.	5.5 x 12.1 x 10.5 in.	5.5 x 12.1 x 10.5 in.	8 x 8 x 4 in.	5 x 14 x 9.5 in
Weight	11 lbs.	11 lbs.	20 lbs.	27 lbs.	7.5 lbs.	21 lbs.	19 lbs.	23 lbs.	16 lbs.	13 lbs.	7.5 lbs.	19.8 lbs.